

Low Voltage Dual Circuit Rail

X01DC

SPEC SHEET



Material: Machined aluminum with electroplated finish.

Sec. Voltage: 12V (fixture).

Mounting: Rotatable and easy to position. Designed for use on MP dual circuit (DC) rail system (sold separately).


Shade: Sold separately.

Stem: Available in 1" (25mm) increments. Maximum length 96" (2438mm).

Accessories: Sold separately.

Lamp (not included): MR16, 50W Max. Covered glass recommended. (Note: GE constant color lamp cannot be used with glass shade.) For use with LED type MR16 check lamp manufacture for specification and compatibility.

Approval: Dry locations. Approved to US and Canadian standards by CSA.



Dimensions reflect 1" (25mm) stem.

Type:
Project:

Modified:

Quantity:
Notes:



cap



metal/glass cone



arc



shroud



louver



filter/spreader

CODE	MOUNT	SHADE*	STEM	ACCESSORIES**	FINISH
X01	DC DC = dual circuit rail	NS = no shade SC = solid metal cap SCB = solid metal cap, black PC = perforated metal cap PCB = perforated metal cap, black SM = solid metal cone SMB = solid metal cone, black PM = perforated metal cone PMB = perforated metal cone, black FR = frosted glass cone AM = amber glass cone BL = blue glass cone MA = mesh arc	1 = 1" (25mm) X = custom length	NA = no accessory SH = metal shroud SHB = metal shroud, black ELB = eggcrate louver, black BE = beam elongator CS = crystal spreader IR = infrared filter MS = mistlite spreader UV = ultraviolet filter LSB = long shroud, black LH = accessory holder***	MC = matte chrome

**Can select multiple items. Please specify.

***Accessory holder required with accessories.



t 1.877.708.1184 f 604.708.1185 www.mplighting.com
16 West 4th Avenue, Vancouver BC V5Y 1G3, Canada

*Note: Shades are not recommended with LED lamps.